

OTR-301-1U



Features

- Holds up to 8 OTR-301 “bullet” Tx or Rx in 1U
- Redundant 90 to 240 VAC power supplies
- Hot-swappable OTR-301
- Up to eight 3G-SDI channels in 1U
- Simple plug and play operation

The OTR-301-1U is a cost effective, 8 slot, 1U chassis for mounting OTR-301 transmitters or receivers in an equipment rack. Clean up the installation by racking up to 8 OTR transmitters or receivers or mix and match in the same chassis. The unit comes standard with a dual 90-240 VAC power supplies and the OTR -301's are hot-swappable. The OTR-301-1U has a quiet operation with no fan and open chassis design for easy installation of transmitters and receivers.



OTR-301-1U

1U CHASSIS FOR OTR-301

Models

Model	Description
OTR-301-1U	19" Chassis, 1U for up to eight OTR-301 "bullet" transmitters or receivers, Redundant 90-240 VAC power supplies

Specifications

Mechanical Specification	
Enclosure type	1U Rack mount
Dimensions (W x H x D)	19" x 1.75" x 10"
Weight	10 lbs
Power Specification	
Power Supply	90-240VAC
Power Consumption	12 Watts (max fully loaded)
Environmental Specification	
Operating Temperature	0 to +50 C
Relative Humidity	0 to 90%, non-condensing
Storage Temperature	-20 to + 85 C

